

Designer CHAIRS

FINISH OFF YOUR CLEVER CRAFT DESK WITH THESE CUTE MATCHING CHAIRS

Wouldn't any kid love these bright, sturdy, kid-size chairs to match their cool craft desk? Better still, they'll be creating their masterpiece on a masterpiece you created! Here's how.

GATHER YOUR SUPPLIES

- 3mm plywood 2440 x 1220mm
- Jigsaw with scroll blade fitted
- Sanding machine OR block
- 15mm plywood 2400 x 1200mm
- Sanding machine OR block
- Router
- Screws
- Drill
- Dulux Duramax Undercoat Spray Paint
- Dulux Duramax Decorative Flat in Vivid White™, Hyssop and Lickedey Lick gloss
- Type 17 decking screws

HERE'S HOW

STEP 1 Using 3mm plywood make a template for chair sides. Mark out chair design and use the base of a can of Duramax as a guide for the rounded ends. Outline with pencil.

STEP 2 Cut the shape of the chair sides out using a jigsaw with scroll blade fitted.

STEP 3 Sand any edges smooth.

STEP 4 Using the template above, mark the 15mm plywood.

STEP 5 Using the jigsaw, cut the chair shape out.

STEP 6 Sand all the rough edges of the timber to smooth out any irregularities.

STEP 7 Using the router with a round over bit, run around all the edges of the plywood on both sides.

STEP 8 Cut the seat and backrest from 15mm plywood.


STEP 9 Round over all edges the same as the sides.



STEP 1



STEP 2



STEP 13

STEP 10 Mark out the position of the screws and predrill these using a countersink tool.

STEP 11 Sand all surfaces prior to painting.


STEP 12 Using the sides as a template, pre-drill where the back and seat will be positioned.

STEP 13 Undercoat using Dulux Duramax Undercoat Spray Paint.

STEP 14 Give a final light sand over all the surfaces.

STEP 15 Apply Duramax Decorative Flat in Vivid White to sides of chairs and Lickedey Lick and Hyssop in gloss to the back and base of chairs and allow to dry.

STEP 16 Screw the chairs together using Type 17 50mm feature stainless screws.



STEP 15

